



Ref.	6DB45
<b>Camera</b>	
Image Sensor	OV4689
	Hi3516D
Resolution	1.5K
Effective Pixels	<b>2688</b> (H) * <b>1520</b> (V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Sync System	External
Usable Illumination	<b>0.01Lux</b>
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
<b>Lens</b>	
Focus Length	<b>2.8-12mm</b>
Focus Control	<b>Manual</b>
Lens Type	Manual
Pixels	<b>4M</b> Pixels
<b>Night Vision</b>	
Infrared LED	∅ 5X30PCS
Infrared Distance	<b>25M</b>
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af

WIFI	N/A
Video Delay	0.3S (Within the Lan)
Main Stream	<b>2688*1520</b> @30fps
Sub Stream	704*576@30fps
IE Brower	IE6-11, Google Chrome(IE Tab), Firefox(IE Tab)
Smart Phone	iPhone, iPad, Android, Android Pad
<b>Camera Features</b>	
Day/Night	Color/ B&W (IR-CUT )
Compression	H.264/JPEG,Support record AVI format.
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
WDR	YES
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
<b>General</b>	
Housing	Vandalproof( metal )
Anti-cut Bracket	Yes, 3-Axis Bracket Built-in for Lens Adjustment
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	∅ 136 x 95(H) mm
Weight	1.1kgs